

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Boise Cascade Corporation		EMERGENCY TELEPHONE NO. 503-963-7131
ADDRESS (Number, Street, City, State, and ZIP Code) P.O. Box 1087, La Grande, Oregon 97850		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS Boise Cascade Particleboard
CHEMICAL FAMILY	FORMULA	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS N/A			BASE METAL N/A		
CATALYST N/A			ALLOYS N/A		
VEHICLE N/A			METALLIC COATINGS N/A		
SOLVENTS N/A			FILLER METAL PLUS COATING OR CORE FLUX N/A		
ADDITIVES N/A			OTHERS N/A		
OTHERS N/A					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Urea-formaldehyde Resin				8	
Inert ingredients: Wood, Water, Wax				92	

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	N/A		
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	LeI	UeI
EXTINGUISHING MEDIA	Water			
SPECIAL FIRE FIGHTING PROCEDURES	None			
UNUSUAL FIRE AND EXPLOSION HAZARDS	None			

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE Unknown

EFFECTS OF OVEREXPOSURE
Irritation to eyes, mucous membranes, shortness of breath.

EMERGENCY AND FIRST AID PROCEDURES

Remove subject; from contaminated area

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Solid - N/A

WASTE DISPOSAL METHOD

No limitations

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

Activated Charcoal Filters

VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES N/A		EYE PROTECTION N/A
OTHER PROTECTIVE EQUIPMENT None		

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

When loading ratio is 0.13 ft² / ft³

(surface ft. of board to cubic of air) & ventilation rate of

OTHER PRECAUTIONS

0.5 air change per hour in a 1,000 cubic ft. room, formaldehyde levels will be 0.3 PPM or less